OSRAM

LEDriving FOG LAMP H8/H11/H16

LED replacement for conventional fog lamps





Extreme bright white light for better visibility

Perfect color match with Xenon and LED headlights



Excellent brightness

No glaring thanks to an optimized light distribution



Matches H8, H11 and H16 halogen lamps

Upgrade to LED with simple plug and play replacement



New OSRAM LED fog lamps to increase safety and performance

The LEDriving FOG LAMP provides an upgrade with SSL technology with a color temperature of 6000K and perfectly matches existing LED Daytime Running Lights and Xenon Low- and High-beam systems. The LED fog lamps are easy to install and fit in most fog headlights using H8, H11 or H16. The advanced airflow technology ensures a long lifetime. The product comes with a 5 year OSRAM guarantee. These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Technical data

Product information

Order reference 66220CW	
Product type (off-road vs. on-road) Off-road ≜ H8/H11/H16	
Application (Category and Product specific)	Mainly used for headlight/ fog light applications


Electrical data

Power input	12.342 W
Test voltage	13.5 V
Power input tolerance	±10 %
Nominal wattage	11.22 W
Nominal voltage	12.0 V

Photometrical data

Color temperature	6000 К
Luminous flux	730 lm
Luminous flux tolerance	±25 %
Light color LED	Cool white

Dimensions & weight



Product weight	145.00 g
Length	470.0 mm
Diameter	42.0 mm

Lifespan

Lifespan Tc	5000 h
Guarantee	4 years
Lifespan B3	2500 h

Additional product data

Base (standard designation)	PGJ19-1/2/3
Capabilities	
Technology	LED

Country specific categorizations

Order reference	66220CW
-----------------	---------

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899465619	LEDriving FOG LAMP	Folding carton box 2	154 mm x 69 mm x 182 mm	1.93 dm ³	477.00 g
4052899465626	LEDriving FOG LAMP	Shipping carton box 4	168 mm x 154 mm x 201 mm	5.20 dm ³	935.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
Z	User instruction LEDriving FOG LAMP 9645CW, 66220CW User manual
太	Brochures Sales Folder LEDriving replacement lamps (EN)
乙	Brochures LEDriving Retrofits - Exchange overview (EN)
太	Brochures 618438_LEDriving RETROFIT application overview (EN)
O	Video OSRAM LEDriving FOG LAMP: Installation tutorial EN

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











