

## LED Floodlight Slim Detect 30W 4000K Black IP65

Bailey nr.: 139844



BAI LED Floodlight Slim Detect Black 30W 4000K 2100lm IP65 IK08 120D 1m MW sensor 2-10m 160D and IR Remote

This Bailey LED floodlight is thin, durable and sturdy and therefore multi-usable. In addition, this aluminum spotlight with safety glass is equipped with a motion sensor where various functions can be set with a remote control (time, distance, radiation). This makes the fixture pre-eminently suitable for use in burglary-prone areas. The luminaire has water resistance class IP65 and is therefore suitable for outdoor use. Cable length 1 meter. Ambient temperature: -25°C to +40°C. Ideal for entrances / exits, (garage) doors, parking lots, gardens etc.

General properties	
EAN-code	8714681398449
Product series	LED Floodlight sensor
Product Type	Slim Detect
Specifications	
Adjustability	Swivelling
With movement sensor	Yes
With light sensor	Yes
With light source	Yes
Lamp holder	None
Material housing	Aluminium
Surface protection	Other
Colour housing	Black
Material cover	Glass transparent
Nominal voltage (V)	220 240 V
Voltage type	AC
LED nominal current at constant current	114 114 mA
Dimmable	No
Light sharing	Symmetric
Beamangle	Extreme wide beam >80°
Rated life time L70/B10 at 25 °C	
Rated life time L70/B50 at 25 °C	30000 h
Rated life time L80/B10 at 25 °C	
Rated life time L80/B50 at 25 °C	
Rated life time L90/B10 at 25 °C	
Rated life time L90/B50 at 25 °C	
Degree of protection (IP)	IP65
Impact strength	IK08
Protection class	I
Rated ambient temperature	-25 40 °C
Max. system power (W)	30 W
Colour of light	Other
Colour temperature (K)	4000 4000 K
Colour rendering index CRI	80-89

00 2100 lm lm/W
)
0 mm
mm
6 mm

