

## Lival GA-016 Standard 34W/930 50D WFL White

Bailey nr.: 142130

Lival LED Tracklight GA-016 Standard 34W/930 3000K 50D WFL White Spot 3-phase adapter

Classic Standard head with an ultra slim track adapter. Simple and efficient – great performance for value. Powder painted die-cast aluminium.



### General properties

EAN-code	8714681421307
Product series	Lival LED Tracklight
Product Type	GA-016 Standard

### Specifications

Adjustability	Rotating and swivelling
With movement sensor	No
With light sensor	No
With light source	Yes
Lamp holder	None
Material housing	Aluminium
Surface protection	Powder coating
Colour housing	White
Material cover	Plastic, transparent
Nominal voltage (V)	220 240 V
Voltage type	AC
LED nominal current at constant current	850 850 mA
Dimmable	No
Light sharing	Symmetric
Beamangle	Wide beam 41-80°
Rated life time L70/B10 at 25 °C	
Rated life time L70/B50 at 25 °C	
Rated life time L80/B10 at 25 °C	50000 h
Rated life time L80/B50 at 25 °C	
Rated life time L90/B10 at 25 °C	
Rated life time L90/B50 at 25 °C	
Degree of protection (IP)	IP20
Impact strength	IK02
Protection class	II
Rated ambient temperature	
Max. system power (W)	34 W
Colour of light	White
Colour temperature (K)	3000 3000 K
Colour rendering index CRI	90-100

### Specifications

Luminous flux (lm)	2775 2775 lm
Lamp efficacy (lm/w)	82 lm/W
Power factor	
Width	84 mm
Height/depth	92 mm
Length	228 mm
Outer diameter	
Built-in height/depth	
Built-in diameter	

**Bailey** 142130

This luminaire contains built-in LED lamps.

A<sup>++</sup>
A<sup>+</sup>
A
B
C
D
E

}

LED

The lamps cannot be changed in the luminaire.

874/2012