

Lival GA-016 Cafeteria 30W/940 30D Flood Silver

Bailey nr.: 144327

Lival LED Tracklight GA-016 Cafeteria 30W/940 4000K 2875lm 30D Flood Silver Railspot 3-phase adapter

Spot with an ultra slim track adapter. Simple and efficient – great performance for value. Powder painted die-cast aluminium.



General properties		Specifications	
EAN-code	8714681443279	Luminous flux (lm)	2875 2875 lm
Product series	Lival LED Tracklight	Lamp efficacy (lm/w)	82 lm/W
Product Type	GA-016 Standard	Power factor	
Specifications		Width	84 mm
Adjustability	Rotating and swivelling	Height/depth	92 mm
With movement sensor	No	Length	228 mm
With light sensor	No	Outer diameter	
With light source	Yes	Built-in height/depth	
Lamp holder	None	Built-in diameter	
Material housing	Aluminium		
Surface protection	Powder coating		
Colour housing	Silver		
Material cover	Plastic, transparent		
Nominal voltage (V)	220 240 V		
Voltage type	AC		
LED nominal current at constant current	850 850 mA		
Dimmable	No		
Light sharing	Symmetric		
Beamangle	Medium beam 21-40°		
Rated life time L70/B10 at 25 °C			
Rated life time L70/B50 at 25 °C			
Rated life time L80/B10 at 25 °C	50000 h		
Rated life time L80/B50 at 25 °C			
Rated life time L90/B10 at 25 °C			
Rated life time L90/B50 at 25 °C			
Degree of protection (IP)	IP20		
Impact strength	IK02		
Protection class	II		
Rated ambient temperature			
Max. system power (W)	30 W		
Colour of light	White		
Colour temperature (K)	4000 4000 K		
Colour rendering index CRI	90-100		

Bailey 144327

This luminaire contains built-in LED lamps.

} LED

The lamps cannot be changed in the luminaire.

874/2012