

LED Floodlight GT Black 100-240V 30W 4000K

Bailey nr.: 90500034262

BAI LED Floodlight GT 30W 4000K 2250lm 100-240V IP65 IK08 Alu housing black 120D 0.5m cable



The Floodlight is also called a spotlight or construction lamp. The Led version consumes little power and lasts a long time so that they are more durable than the traditional predecessors. Can be mounted on both wall and ceiling. The housing is made of cast aluminum. Comes with 50 cm connection cable. Suitable for ambient temperatures from -10 ° C to + 40 ° C. Consult specifications and warranty for installation.

General properties

EAN-code	8714681342626
Product series	LED Floodlight
Product Type	GT

Specifications

Adjustability	Swivelling
With movement sensor	No
With light sensor	No
With light source	Yes
Lamp holder	None
Material housing	Aluminium
Surface protection	Other
Colour housing	Black
Material cover	Glass transparent
Nominal voltage (V)	100 240 V
Voltage type	AC
LED nominal current at constant current	
Dimmable	No
Light sharing	Symmetric
Beamangle	Extreme wide beam >80°
Rated life time L70/B10 at 25 °C	
Rated life time L70/B50 at 25 °C	50000 h
Rated life time L80/B10 at 25 °C	
Rated life time L80/B50 at 25 °C	
Rated life time L90/B10 at 25 °C	
Rated life time L90/B50 at 25 °C	
Degree of protection (IP)	IP65
Impact strength	IK08
Protection class	I
Rated ambient temperature	-10 40 °C
Max. system power (W)	30 W
Colour of light	Other
Colour temperature (K)	4000 4000 K
Colour rendering index CRI	60-69

Specifications

Luminous flux (lm)	2250 2250 lm
Lamp efficacy (lm/w)	75 lm/W
Power factor	
Width	178 mm
Height/depth	81 mm
Length	215 mm
Outer diameter	
Built-in height/depth	
Built-in diameter	

Bailey 90500034262



This luminaire contains built-in LED lamps.



LED

The lamps cannot be changed in the luminaire.

874/2012

